

**HIGH-POWER**  
**SOLID STATE**  
**LED** *RETROFIT*  
*LAMPS*



**TOPAZ**  
**LIGHTING**

Friendly Service... Powerful Solutions™

## Smooth Sided BR Lamps

**Applications:** Hospitality Industry such as Hotel Rooms, Lobbies, Conference Rooms and Other Commercial Indoor Locations. Fits Standard Recessed Downlighting Fixtures for Architectural, Residential and Light Commercial Applications.

**Benefits:** Energy Saving, Excellent Color and Light Quality, 10 times the Life of a Standard Incandescent Lamp, NO Mercury Content or UV Emission, Fully Dimmable, Great Replacement for Incandescent and Halogen Lamps, especially in hard to Re-lamp Locations.

**Features:** 120V, E26 Medium Base, 80 CRI, 3000K Warm White, 25,000 Hour Life.

### **LR20WW/8/D**

8W  
520 Lumens  
Replaces 50R20  
MOL: 3.9"  
**Dimmable**



### **LBR30WW/11/D**

11W  
750 Lumens  
Replaces 65BR30  
Available in:  
GU24 (Shown) - MOL: 5.2"  
and Medium Base - MOL: 4.5"  
**Dimmable**



## **LBR40WW/13/D**

13W  
880 Lumens  
Replaces 85BR40  
MOL: 6.5"  
**Dimmable**

## **LBR40WW/18/D**

**Available Summer 2013**

18W  
1230 Lumens  
Replaces 120BR40  
MOL: 6.5"  
**Dimmable**



## **Finned Heat Sink Style BR Lamp**

## **LBR30WW/15/D**

15W  
750 Lumens  
Replaces 65BR30  
40,000 Hours  
MOL: 5.3"  
**Dimmable**



## Wet Location PAR38 Lamp

**Applications:** Outdoor Landscape and Security Fixtures.

**Benefits:** Energy Saving 17W Replaces Halogen 75W PAR38 at 10 times the Life of Comparable Halogen/Xenon Lamps.

**Features:** Dimmable, UL Wet Location Listed.

### LP38WW/17/FL/DC

40° Flood Light  
3000K Warm White  
Cree Chip  
880 Lumens  
82 CRI  
25,000 Hours  
MOL: 5.25"  
**Dimmable**



**CREE**   
LEDs



## "GBF" Replacement Lamp

**Applications:** Low Voltage Indoor Downlighting. Great Replacement for Elevators.

**Benefits:** Uses 1/6<sup>th</sup> of the Energy and Lasts 12 times as Long.

**Features:** 3W equals 20 Watt Halogen - Replaces 20ALR12.

### LGBF/WW/3/FL

30° Beam Spread  
CREE Chip  
3000K Warm White  
115 Lumens  
12V  
25,000 Hours  
MOL: 1.75"

**CREE**   
LEDs



## MR11 12V

### LM11CW/3/NFL

25° Narrow Flood  
Equals 20W Halogen  
5000K Cool White  
Cree Chip, 3W, 12VAC  
25,000 Hours, 160 Lumens  
1 Diode  
MOL: 1.5"

### LM11WW/3/NFL

25° Narrow Flood  
Equals 20W Halogen  
3500K Warm White  
Cree Chip, 3W, 12VAC  
25,000 Hours, 140 Lumens  
1 Diode  
MOL: 1.5"



**CREE** LEDs

## MR16 12V

### LM16WW/6/FL

Equals 35W Halogen  
40° Flood Light  
3000K Warm White  
6W, 12V  
25,000 Hours, 250 Lumens  
3 Diodes, 80 CRI, GU5.3 Base  
MOL: 2"

### LM16CW/6/FL

Equals 35W Halogen  
40° Flood Light  
6000K Daylight  
6W, 12V  
25,000 Hours, 300 Lumens  
3 Diodes, 71 CRI, GU5.3 Base  
MOL: 2"



## MR16 120V GU10

### LGU10WW/4/C

20° Beam Spread  
Equals 20W Halogen  
3300K Warm White  
4W, 120V  
25,000 Hours, 180 Lumens  
3 Diodes, 80 CRI  
CREE Chip, GU10 Base  
MOL: 2.2"

### LGU10CW/4/C

20° Beam Spread  
Equals 20W Halogen  
6000K Daylight  
4W, 120V  
25,000 Hours, 200 Lumens  
3 Diodes  
CREE Chip, GU10 Base  
MOL: 2.2"



**CREE** LEDs

**UL** LISTED

# LED DECORATIVE AND HOUSEHOLD REPLACEMENT LAMPS

## Candle Style Lamps

**Applications:** Hospitality and Residential Applications.

**Benefits:** Use in Chandeliers, Wall Sconces, Ceiling Fans, Carriage Lamps and Lanterns. Ideal in Hard to Reach Locations.

**Features:** 120V, Warm White, 30,000 to 35,000 Hour Life – 30 to 35 times Incandescent Life!

### **LB10WW/2/C/E12**

2W (1.6W) Equals 15W Incandescent  
E12 Candelabra Base  
B10 Shape, Clear Finish  
100 Lumens  
MOL: 3.75"

### **LB10WW/2/C/E26**

2W (1.6W) Equals 15W Incandescent  
E26 Medium Base  
B10 Shape, Clear Finish  
100 Lumens  
MOL: 3.75"

### **LCFC/WW/3.5/D**

**Available Summer 2013**

3.5W Equals 40W Incandescent  
E12 Candelabra Base  
CA12 Shape, Clear Finish  
350 Lumens  
MOL: 4.6"  
**Dimmable**



## Dimmable Torpedo and Flame Tip Candles

All E12 Candelabra Base Candles below come with an E26 Adaptor in box.

### **LCFC/WW/2/CD**

2W Equals 15W Incandescent  
CA10 Shape, Clear finish  
Flame Tip, 100 Lumens  
MOL: 4.7"

### **LCFF/WW/2/CD**

2W Equals 15W Incandescent  
CA10 Shape, Frost Finish  
Flame Tip, 90 Lumens  
MOL: 4.7"

### **LCTC/WW/2/CD**

2W Equals 15W Incandescent  
B10 Shape, Clear Finish  
Torpedo, 100 Lumens  
MOL: 4.1"

### **LCTF/WW/2/CD**

2W Equals 15W Incandescent  
B10 Shape, Frost Finish  
Torpedo, 90 Lumens  
MOL: 4.1"



# LED DECORATIVE AND HOUSEHOLD REPLACEMENT LAMPS

## General Service Lamps

**Applications:** Hospitality and Residential Applications. Use in Base Up Applications such as Lanterns, Garages, Utility and Laundry Rooms, Closet and Storage Areas.

**Benefits:** 180 Degree Cutoff in Base Up Position, Suitable for Dark Sky Environments. 25 times the Life of a Standard Incandescent While Using 1/5<sup>th</sup> of the Energy!

**Features:** Dimmable, 120V, Frost Finish, Warm White, 80 CRI, 25,000 Hour Life.

### LA19WW/8/F/D

3000K, 8W, 470 Lumens  
Equals 40W Incandescent  
MOL: 4.3"

**Dimmable**

### LA19WW/10/F/D

**Available Summer 2013**

2700K, 10W, 800 Lumens  
Equals 60W Incandescent  
MOL: 4.4"

**Dimmable**

### LA19WW/8/F/GU24/D

3000K, 8W, 470 Lumens  
GU24 Base  
Equals 40W Incandescent  
MOL: 4.2"

**Dimmable**



## LED T8 LAMPS

### 4' T8 Lamps

**Applications:** Replaces Linear Fluorescent T8 Lamps in Office, Retail, and Warehouse Applications.

**Benefits:** Energy Saving, Twice the Life of a Standard Fluorescent Lamp, PC Lens and Aluminum Heat Sink Eliminates the Need for Tube Guards or Safety Shielded Lamps. No Mercury Content or UV Emissions.

**Features:** Single End Power, Universal Voltage, 120/277 VAC, 50,000 Hour Life

### L4T8/40/20/U/G2

20W  
2' Available by Request  
3500K, 4000K, 5000K and 6500K  
Choice of Clear or Frosted Lens  
1800 to 2000 Lumens; Varies by CCT/Finish  
MOL: 48"



### L4T8/40/20/U/KIT

**Available Summer 2013**

22W  
2-Pack  
4000K and 5000K  
Clear Only  
2300 Lumens  
DLC Qualified  
MOL: 48"

